

# MS ROLLING SHUTTER WITH ASIAN SIDE MOTOR



Toshi manufactures a large range of Automatic MS Rolling Shutters for all commercial and industrial applications. All our Rolling Shutters are automatic using vigorous drive expertise with manual override in case of power failure and are dense, noiseless, and dependable with low decibel level. Our rolling shutters conformity with new and demanding building requirements has always been our major objective. All parts of our quality rolling shutter are created in our own unites.

# TECHNICAL DATA

<b>Width min./max.</b>	1000/12000 mm
<b>Height min./max.</b>	1000/14000 mm max. area 120.0 sqm
<b>Opening direction</b>	Vertical
<b>Wind resistance up to</b>	90 km/hr *higher wind pressure on request
<b>Opening/closing speed</b>	0.05 m/sec - 0.1 m/sec

<b>Slat Material</b>	M.S/G.I steel stats available in 0.9 mm, 1.0 mm & 1.2 mm thickness
<b>Side Guide Profile</b>	Mild steel/gi side guides 75 mm
<b>Roller Shaft</b>	Heavy duty mild steel strong suspension tubular shaft without springs
<b>Side Brackets</b>	M.S plate 3 mm to 10 mm, as per the opening dimension

## FEATURES AND BENEFITS OF THE OPERATOR :

<b>Features</b>	<b>Benefits</b>
High-speed opening & closing	Faster movement of traffic
User friendly interface	Easy to use
Tubular seal	Noise free movement
Bend-resistant MS profile	Long lasting
Safety	No damages/no accidents