## Automatic Bollard (TASPL - 300/12)



Toshi bollards are perfect for all light security needs where a retractable option is necessary. From traffic control to limited access pathways, this bollard is the obvious choice for ease of use and economical, maintenance-free operation. The bollard lifts easily and locks into place and just as easily can be retracted for pedestrian safety. The Toshi bollard can be embedded in concrete for simple and secure installations. Its clean and versatile design is highly visible with consistent aesthetics that suit any modern building or landscape. High-quality Mild steel with satin finish features high resistance to corrosion and weathering.





## **Technical Data**

Model			TASPL 300/12
System control	Electric hydraulic pressure		
Max load capacity			3600 kg
Power			220 V
System dynamic pow		ver	1.5 kW / 2.2 kW
Rise/lower			10 to 12 seconds

Time	(adjustable)
Working temperature	-10 °C to 75 °C
Lifting height	700 mm
Wall thickness	12 mm
Diameter	273 mm
Weight	Up to 180 kg

<sup>\*</sup> Technical Specifications are subject to change without notice

## Featires and Benefits of the operator:

Features	Benefits	
High-speed opening & closi	ng Faster movement of traffic	
LED warning lights	For night time operation	
Energy efficient design	Less power consumption & money saving	
Compact	Less space required	
Sealed housing	Eliminates dust and moisture	
Durable	High load-bearing design	