

Hydraulic Road Blocker



Model : HYTL20

- Hydraulic road blocker is HIGH END SECURITY PRODUCT used for protection against unwanted vehicles ramming into important and strategic places like Hospitals, Hotels, Government Buildings, Schools, Defence Establishments, Embassies, Factories etc.



Main Technical parameters:

- 1) Passing capability: HYTL20.HYTL25.HYTL30. HYT35 type can allow 70 ton container trucks passing.
- 2) HYTL 750 type can allow 60 ton vehicle passing.
- 3) Power supply: 1.5KW/380V. 3 PHASE
- 4) Dropping-time: ≤3 SECONDS
- 5) Lifting-time: ≤4S (HYTL 750 about 5s)
- 6) Operating environment temperature: -25°C~65°C
- 7) Storage environment: -10°C~75°C. Road Blocker is water proof, dust proof,
- 8) Standard: Please see the table enclosed for various models available.
- 9) Material: Special Steel for Anti Terrorism with Anti Rust Paint
- 10) Weight: 0.75~1.0 ton

Operation :

Mechanical : Unit consists of 3 phase Motor, Hydraulic Pump, Valve system.

Electrical : All things are controlled by Three Phase Controller to open – lower the Hydraulic Road Blocker Flashing Lights/ Alarms/ Boom Barriers can be connected with Controller Unit so when Road Blocker is going down, boom goes up, Lights are flashing and Alarm is Buzzing. FOR ROAD WIDTH BIGGER THAN 3500MM, Two units can be mounted to cover the Road Length.

Specification Type	External dimension	Movable Cover Lifting
HYTL20	L2260*W780*H700	350
HYTL25	L2500*W780*H700	350
HYTL30	L3000*W780*H700	350
HYTL35	L3500*W780*H700	350
HYTL750	L3210*W1156*H808	750



ASCION ENTERPRISE

77A/ 22, Raja S. C. Mullick Road, Kolkata- 700092
 Tel: 033 2413 7160 M# +91 98300-39931 / 94335-56655 / 90736-79221
 e-mail : asconsanjib@gmail.com Web. www.asconenter.com