



Industrial Sectional Door



Industrial Sectional Doors

are vertically-opening doors constructed using multiple panel sections built to withstand heavy usage using double skinned steel foam filled panels in the main but also aluminum framed and glazed panels for varying degrees of high quality vision. The vertical opening of these doors creates more space in front of and behind the door allowing you to park vehicles closer and utilize more room inside the building. When open, the industrial door sections neatly fold up and lay flat beneath the ceiling. For angled roofs, special tracks can be ordered so that the door panels open in line with the roof and you can even have a sectional door foing straight up the wall vertically if you have the headroom.

Technical Data

Panel thickness	40 mm	Water tightness	1 Class (water from 30 Pa)
Galvanized sheet	0.4 mm on both sides of panel	Operating voltage	220 V AC
Lift type	Horizontal	Spring break protection device	Included
Heat conductivity	0.38 W/m °C	Standard colour	Ral 9003(white) on both sides
Weight	17 kg per square meter	Step handle	1 Nos. included

* Technical Specifications are subject to change without notice



Features	Benefits
High-speed	Time saving
Heat conductivity	Maintains temperature
Pedestrian	Less power consumption
Compact	Less space required
Safety	Easy to use

TASPL 174588

ASCION ENTERPRISE

77A/ 22, Raja S. C. Mullick Road, Kolkata- 700092
Tel: 033 2413 7160 M# +91 98300-39931 / 94335-56655 / 90736-79221
e-mail : asconsanjib@gmail.com Web. www.asconenter.com